



Ctra. Nova 129 3<sup>o</sup> 4<sup>a</sup> La Garriga 08530 Barcelona

Telf. 603037788

Email. [info@crovay.com](mailto:info@crovay.com)

[www.crovay.com](http://www.crovay.com)

### **Technical Data Sheet**

## **ROSEMARY VERBENONE OIL**

Reference : ROSEMARY VERBENONE OIL

### **TECHNICAL DATA**

<i>Relative density (d20/20) :</i>	[0.895 ; 0.925]
<i>Refractive index at 20°C :</i>	[1.467 ; 1.477]
<i>Angular rotation (°) :</i>	[-4 ; +39]
<i>Color :</i>	very pale yellow to light yellow
<i>Appearance :</i>	liquid
<i>Odor :</i>	fresh, warm.
<i>Flash point (° C) :</i>	+36° C
<i>Manufacturing process :</i>	obtained by steam distillation of the branch of Rosmarinus officinalis CT verbenone.
<i>I.N.C.I :</i>	ROSMARINUS OFFICINALIS LEAF OIL
<i>Description :</i>	natural product according to council directive 1334/2008 EEC.

### **TRANSPORT-STORAGE**

<i>Custom tariff :</i>	33012941
<b>STORAGE</b>	Store product in full, tightly closed containers

# ROSEMARY VERBENONE OIL

## LEGISLATION :

FEMA : 2992  
COE : 406n  
EINECS : 283-291-9  
FDA : 182.20  
C.A.S : 8000-25-7 84604-14-8

## Labeling :



AH1 Aspiration hazard 1  
AT14 Acute toxicity inhalation 4  
EHA1 Hazardous to the aquatic environment, acute hazard 1  
EHC1 Hazardous to the aquatic environment, long-term hazard 1  
FL3 Flammable Liquids 3  
SS1A Sensitisation, skin 1A  
STO-SE2 Specific target organ toxicity, single exposure 2



H226 - Flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H317 - May cause an allergic skin reaction.  
H332 - Harmful if inhaled.  
H371 - May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H400 - Very toxic to aquatic life.  
H410 - Very toxic to aquatic life with long lasting effects.  
  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P241 - Use explosion-proof electrical/ventilating/lighting/.../equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.